



STRUMENTOMARINO.COM

User Manual Japan Miyota 6510





A) SETTING THE TIME



- 1. Pull the crown out to the third position.
- $2.\,Turn$ the crown to set hour and minute hands.
- 3. After the time has been set, push the crown back to the regular position (1).

B) SETTING THE DATE

- 1. Pull the crown out to the second position.
- 2. Turn the crown clockwise to set the date.
- $^{*}\mbox{If}$ the date is set between the hours of around 9:00 PM and 1:00 AM the date may not change on the following day.
- 3. After the date has been set, push the crown back to the regular position (1).

C) USING THE STOPWATCH

This chronograph is able to measure and display time in1/20 second united up to maximum of 59min 59 sec. The chronograph 1/20 second hand keeps continuously for 30 seconds after starting and then stops at Zero position. Stopwatch will stop automatically after running continuously for 31 minutes.



[Measuring time with the stopwatch]

- 1. Press button "A" to start the stopwatch.
- 2. The stopwatch can be started and stopped each time button "A" is pressed.
- 3. Press button "B" to reset the stopwatch and stopwatch minute and second hands return to their [1] positions.

D) CHRONOGRAPH RESET (INCL. AFTER REPLACING BATTERY)

This procedure should be performed when the stopwatch second θ minute hand does not return to the [0] position.

- 1. Pull the crown out to the third position.
- 2. Press the button "A" once to set the chronograph second hand to the Zero position.
- *The chronograph hands can be advanced rapidly by continuously pressing button "A".
- 3. Once the hands have been set at Zero position, reset the time and return the crown to its regular position (1).